

SAVO SOUL



Office seating

Savo Soul is a complete family of office chairs aiming to fulfil all needs of a modern office environment.

Choose between the two mechanisms:

- A6, for multiple users where adjustment needs are few. The adjustment of the back rest's resistance is automatically adjusted based on the weight of the user.
- M6, the full multi-dynamic solution where the chair follows all your movements. The few needed adjustments are easy to handle and intuitive.

Savo Soul is designed by Olle Lundberg.

Functions

- Savo floating Tilt®, independency between seat and backrest.
- Adjustable seat height, seat depth and back height.
- Automatic tilt resistance (M6 can also be adjusted more).
- Backrest angle lockable in several positions.

Choices

- Upholstered seat. Upholstered backs in 3 heights: 40 cm, 50 cm and 60 cm. Upholstered seat and mesh back 50 cm.
- Adjustable seat height 400-520 mm as standard. Additional 500-630 mm or 430-550 mm.
- Adjustable armrests: 2D in width and height 180-280 mm from seat. 4D in width, height 210-310 mm from seat, depth and angle adjustable 180 degrees.
- Adjustable head support in height and depth.
- Base in black plastic (standard) or polished aluminium (additional).
- Unbraked castors for hard floors as standard. Castors for soft floors, intervallic braked castors and lockable castors (when loaded) as additional.

Quality

- Declared according to EN 1335-1 type A & B, EN 1335-2, EN 1335-3.
- Savo offer 10 years warranty for manufacturing defects at regular 9-hour sitting. For chairs in fabric 24/7, which is used for 24-hour sitting, we offer 2 years warranty for manufacturing defects. The warranty does not cover fair wear and tear. The warranty covers parts, not working costs. Savo does not give warranty on customer's own material.



Upholstered back (40)



Upholstered back (50)



Upholstered back (60)



Mesh back (50)

Measurements

Model	Seat height std.lift	Seat		Backrest		Armrests height from seat	Seat depth regulation	Base diameter
		Width	Depth	Width	Height			
A6 mesh	400-520	475	490	420	590	-	420-500	Ø 660
A6 40	400-520	455	450	400	480	-	390-470	Ø 660
A6 50	400-520	475	490	420	590	-	405-485	Ø 660
A6 60	400-520	475	490	420	670	-	410-490	Ø 660
M6 mesh	400-520	475	490	420	590	-	420-500	Ø 660
M6 40	400-520	455	450	400	480	-	390-470	Ø 660
M6 50	400-520	475	490	420	590	-	405-485	Ø 660
M6 60	400-520	475	490	420	670	-	410-490	Ø 660